

# FAAC Safe Flow BASE

**FAAC**  
Simply automatic.



The status LED is always on and updating in real time with the status of the traffic light.



**The Safe Flow BASE** is an easy, efficient and cost effective solution, perfect for those applications where a manual control is required.

## Applications

Ideal for the small corner or high street shop, surgeries, chemists, small post office, the list is endless.

## Function

The system requires the manual switching of the Traffic Light to allow, or prevent, entry into the premises. The Safe Flow BASE can be used at the store entrance or to control separation in areas inside a bigger premises.

It's simplicity allows quick and easy deployment and this stand-alone option requires **no cables or permanent fixings**, and can easily be packed away at the end of the day.

## How to use the Safe Flow Base

Position the traffic light at the door entrance and the transmitter at a convenient location on the counter or reception desk. Switch on both devices, the connection is automatic. The Bi-directional radio control allows you to check the current status of the traffic light signal on the remote .



Remote Control

Check the capacity and switch the traffic light to green or red to control the entry of additional people.

## Safe Flow BASE part no. UK-QMANAGER-BG

Kit comprises:

1 x Pole, 1 x Base 1 x Traffic light head with red and green LED's with integrated battery pack, 1 x Sign, 1 x System receiver, 1 x bidirectional remote transmitter with rechargeable batteries, 1 x Power cable/battery charger



TECHNICAL FEATURES	
Dimensions	Height: 145 cm Base 40 x 30 cm
Weight	12 Kg
Power supply	230V ac 50-60Hz
Power	0,4A
Radio range	30m
Frequency	WiFi 2.4Ghz
Remote control Battery Life	lithium rechargeable: approx. 15 hours operation
Lens Diameter	125mm
Brightness	60Lm
Maximum remotes	100

## Optional Extras

- An audible warning "Please Wait" Can be added to the system
- Additional Remote controls can be added to the system. A quick and easy App wizard allows pairing to an existing system.
- Can be used with any new or existing FAAC Automatic Swing or Sliding door system.
- The BASE unit can be interfaced with the automatic door control board and manage the external activator. (subject to exiting sensor technology)
- Plug and Play, the system is provided ready to use, additional accessories are subject to a simple pairing procedure, using a friendly App for smartphone or tablet.
- Battery operated
- Rechargeable batteries allow 15 hours of continuous use on a 7 hour charge.