FAAC A951 DDA

Simply automatic.

Automatic Toilet Door System

The FAAC A951 DDA Automatic Toilet Door System now with Touchless/Contactless Activation switches to prevent the transmission of the Covid-19 virus, the system comprises Operator, Push/Pull Arm, Safety Sensors, Finger-guard, Signs and the failsafe magnetic locking system in one simple and easy to install kit.

The Disabled person's toilet door system can easily be integrated into an existing or new swing door and delivers a comfortable and easy to use solution, whilst providing compliance with Disability Discrimination Act 1995.

Operation is by two contactless Sensors that control the entry cycle by automatically opening and then locking the door and the exit cycle by unlocking and opening the door at the appropriate times interfacing with both the A951 automatic door operator and an electromechanical locking device. An emergency 1 - Entry override keyswitch is also included in the kit.



What's in the kit?

1 x 105951 A951 Automatic Door Opener with Push or Pull Arm systems (Please state "PUSH or PULL at time of ordering)

- 1 x A951 Battery pack
- 1 x 340mm BEA 4Safe external door sensor
- 1 x 900mm BEA 4Safe internal door sensor
- 1 x White hinge door Finger guard
- 2 x Automatic door stickers
- 1 x Keep Clear stickers
- 1 x Toilet door pack including contactless Activation sensors

Please note, this system is ONLY for use on doors up to 1100mm wide.

All work undertaken on Automatic Doors must comply with the appropriate standards.

Optional round sensors available, please state upon ordering which type are required.

Contact: Robin Palmer 07818 595 199 robin.palmer@faac.co.uk



How it works:

Wave your hand in front of the entry sensor on the outside of the toilet. The A951 Operator will automatically open the door to provide access.

2 - Lock

Wave your hand in front of the Red sensor on the inside to close and lock the door. To confirm the door is locked, the indicators on both Sensors will flash showing the toilet is engaged and inhibiting the entry sensor.

3 - Exit

Wave your hand in front of the Green sensor on the inside and the indicator stops flashing. The door will unlock and the A951 Operator will automatically open the door. The entry sensor on the outside will stop flashing and becomes operable once again to provide access for the next user.







optional round sensor version